

According to the Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

**A. N.C.I. Servizi s.r.l. a socio unico - sezione C.I.M.A.C.
Community Identification N° 0465**

Grants:
Manufacturer
COFRA S.R.L.
VIA DELL'EURO 53-57-59
76121 BARLETTA

EU TYPE-EXAMINATION CERTIFICATE MODULE B
N° F-100-02311-19

for the following model of Personal Protective Equipment:

Design/ Article: Half-knee boot art. CAMBER - 1103
Category of PPE: II
Additional requirements: S3 CI SRC

safety footwear for professional use according to harmonized standard (*)
EN ISO 20345:2011

Picture of the basic model



First issue date: 11/06/2019
Revision date:
Expiry date: 11/06/2024

Technical Responsible
Giuseppe Bellotti



EU Type-Examination Certificate n. F-100-02311-19 of 11/06/2019 - Page: 1 of 3 2019\1274-9

A.N.C.I. Servizi s.r.l. a socio unico
CIMAC Laboratories

CF e PIVA 07199040150 – REG. Imprese n° 229059 Trib. Di Milano – REA n° 1147818
Tel. 0381.84722 – Fax. 0381.73393 – email: info@cimac.it – web: www.cimac.it
Sede Legale:
Via Alberto Riva Villasanta, 3
20145 Milano - ITALY

Sede Operativa:
C.so Giacomo Brodolini, 19
27029 Vigevano (PV) - ITALY

Sede Operativa:
Via Aguzzafame, 60/b
27029 Vigevano (PV) - ITALY

Manufacturer's identification mark:	COFRA		
Classification:	I - Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear		
Size range:	from 36 to 48 (french point)		
Identification of last:	5717		
Manufacturing process:	Injection		
The footwear has a:	metallic toecap	cod	AAAMN - SAFIT AM)
	non-metallic penetration-resistant insert	cod	OSAZC.xxx.F03 (TEXON KNOX)
	removable insock	cod	SP181
Additional requirements:	heel area closed;		
	A	antistatic properties;	
	E	energy absorption of seat region;	
	WRU	water resistant upper	
	P	penetration resistance of sole complex;	
	CI	cold insulation of sole complex;	
	FO	fuel oil resistant outsole;	
		cleated outsole.	

Test Reports: The results of tests and examinations are contained in the following test reports:

CIMAC	RP 2019\1274-9-RP-2	dated	11/06/2019
CIMAC	RP 2019\1274-9-RP-3	dated	11/06/2019
CIMAC	RP 2018\2275-5-RP-2	dated	10/10/2018
CIMAC	RP 2018\2275-5-RP-4	dated	10/10/2018
CIMAC	RP 2018\2301-5-RP-4	dated	23/10/2018
CIMAC	RP 2017\2479-1-RP-2	dated	24/11/2017
CIMAC	RP 2017\2479-1-RP-4	dated	24/11/2017
CIMAC	RP 2018\3483-3-RP-2	dated	02/04/2019
CIMAC	RP 2018\3483-3-RP-4	dated	02/04/2019
CIMAC	RP 2017\2005-2-RP-2	dated	02/10/2017
CIMAC	RP 2017\2005-2-RP-4	dated	02/10/2017
CIMAC	RP 2018\0973-1-RP-2	dated	15/05/2018
CIMAC	RP 2018\0973-1-RP-4	dated	15/05/2018
CIMAC	RP 2017\2005-1-RP-2	dated	02/10/2017
CIMAC	RP 2017\2005-1-RP-4	dated	02/10/2017
CIMAC	RP 2016\1539-1-RP-2	dated	03/08/2016
CIMAC	RP 2016\1539-1-RP-3	dated	03/08/2016
CIMAC	RP 2016\1539-1-RP-4	dated	03/08/2016

Marking

The PPE shows the following information:

- CE Marking (at least 5 mm high)
- Name and postal address of the Manufacturer
- manufacturer's type designation
- the number and year of the reference European standard
- Category and additional requirements of the PPE
- Month and year of fabrication
- Size
- Batch number
- Reference of informative note

(*) Subsystems and safety components which are in conformity with harmonised standards or parts thereof the references of which have been published in the Official Journal of the European Union shall be presumed to be in conformity with the essential requirements set out in Annex II Regulation (EU) 2016/425.

Validity conditions: This certificate is valid for 5 years from the date of issue. On expiration the manufacturer shall ask for its renewal.

The rules applied are those in force on the date of issue shown on this certificate; The validity of the certificate is no longer guaranteed if substitutive standards are issued before the expiration date.

All changes made to the model and to the materials described in this EU type-examination certificate shall be reported to and approved by CIMAC.

This EC Type-Examination Certificate may be integrally duplicated; the copy must be faithful, legible (if pint size) and must contain the bold caption "TRUE COPY".

This certificate must be kept by the manufacturer to be shown, on request, to the inspection or notifying authorities.