



PRODUCT NUMBER: 1013205
**Honeywell SuperOne 3205 -
FFP2 NR D**

Honeywell

Overview

Reference Number

1013205

Product Type

Respiratory Protection

Range

Disposable APR

Line

Moulded masks

Brand

Honeywell

Brand formerly known as

WILLSON

Industry

- Agriculture
- Automotive and Part Manufacturer
- Building and Construction
- Food Industries
- Foundry
- Iron and steel industry
- Mining and Quarrying
- Textile Industries
- Wood Industries

Product Use

Application: Textile, mining, construction, iron and steel industries, car body preparation industry, woodworking, agricultural and horticultural activities, food industry, cutting and moulding of metals, etc ... Protects against dusts, mists and fumes containing calcium carbonate, clay, kaolin, cellulose, cotton, flour, ferrous metals, cement, sodium silicate, sulphur, glass fibers and plastics, hardwood, coal, quartz, non ferrous metals, copper, aluminium, barium, titanium, vanadium, chrome, manganese, molybdenum, vegetal and mineral oils, metal-working fluids (this list is non-exhaustive).

Maximum usage level: can be used in atmospheres containing solid and/or liquid aerosols in concentrations up to 12 (10 in UK, FIN, D, I, S) x WEL*: FFP2 class (average toxicity). "NR" (Non Reusable) marked, it can be used one single shift (according to EN 149:2001+A1:2009). Certain restrictions or limitations may apply in the case of specific contaminants. Please refer to applicable health and safety standards.

Limitation to use:

This single-use filtering half-mask should NOT be used in the following situations :

- oxygen concentration is less than 17% (oxygen-deficient atmospheres)
- contaminants or their concentrations are unknown or are immediately dangerous to life or health
- contaminants concentrations exceed levels fixed by applicable health and safety standards or 12 (10 in UK, FIN, D, I, S) x WEL*
- in the presence of toxic or radio-active contaminants
- in the presence of gases or vapours

- fire fighting.

Caution:

We recommend users to ensure that the level of protection offered by the respirator is sufficient for the type and concentration of contaminant(s) in the work area.

For use only by trained and qualified personnel.

Leak-tightness is unlikely to be achieved if the mask is worn against a beard or facial stubble.

This respirator does not supply oxygen.

* WEL : Workplace Exposure Limit.

Features & Benefits

Feature

Exclusive design and shape: semi-rigid mask, designed to stay maintained in time. Upper part pre-formed (no nose-bridge) for a quick and easy adjustment, highly efficient and secure. Great inner volume to avoid any oppression on face and to ease communications. Ultra-soft inner veil to offer a soft and pleasant contact to the skin and improve the breathing comfort. Twin supple and resistant elastics, stapled on ear tabs to avoid any risk of irritation and of leakage in the filtering area. Ultra-light(8g) to minimize wearer fatigue and increase acceptance in time. No latex, no silicone, no PVC
 Viral Filtration Efficiency > 99,9% (These results do not constitute a warranty. Single-use masks are personal protective equipments. They intend to filter and not to kill viruses. To obtain the maximum protection, It is IMPERATIVE, to read and understand the product information featuring on the insert before fitting the masks).

Benefit

- Designed to fit everyone. - Easy to use, comfortable and secure. - Time saved due to minimum adjustment required. - Breathing comfort is optimised - Compatibility with spectacles - Excellent field of vision - Prevents irritations - No risk of allergies to latex - No restrictive use - Environment-friendly

Technical Description

Standard

EN149.2001

Mask Type

Molded Cup

Protection Class

FFP2

Valve

No

Straps

Double elastics

Mask Size

Medium

Latex Free

Yes

PVC Free

Yes

Silicone Free

Yes

Certifications

EU Category PPE

3

Quality Assurance

ISO 9001 / 2000

EU Certification

0082/236/079/03/19/0334

Certifications

- EN 149:2001+A1:2009

Literature & Documents

90025793-01_SuperOne_29L_EAC_HonNorth

http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/respiratory_protection/4295003426/1033.aspx

Maintenance

Life Cycle

3 years

Storage Information

Temperature range of storage conditions: -20°C/+40°C

Maximum relative humidity of storage conditions: less than 95 %

Packaging

Quantity per Box/Pack/Case

30, 300, 8 100