

Notified body N° 0075

#### **EC-TYPE EXAMINATION CERTIFICATE**

The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N°

0075/1602/162/05/16/0477

Is given to the following model of personal protective equipment :

Issued to:

**ODIBI SRL** 

Via Venezia, 35 - 33085 Maniago (PN), Italy

Italy

Distributor:

1

Product reference:

16874

**Description:** 

PPE Type:

Protective gloves against

mechanical risks.

Reference standard:

EN 388 : 2003.

Category:

11

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the complete certificate N°0075/1602/162/05/16/0477.

Issued in Lyon by Lionel Gaudillere

Head of CE marking

Date of issue: May 12th, 2016



In application of the Directive ref 89/686/EEC of the 21th December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decree N°92-765, 766 and 768 of the 29th July 1992 concerning the transposition of this Directive into French law.

CTC is notified by decree of the Ministry of work of the 20th December 2010 and is registered under the number 0075 in OJEU.









In application of the Directive ref. 89/686/EEC of the 21<sup>st</sup> of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29<sup>th</sup> of July 1992 concerning the transposition of this Directive into French law,

#### CTC

4,rue Hermann Frenkel - 69367 Cedex 07 - France
Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr

authorized by decrees of the Ministry of Work, Employment and Health of the 20<sup>th</sup> of December 2010, registered under the number 0075, published in OJEC, delivers:

# EC-TYPE EXAMINATION CERTIFICATE 0075/1602/162/05/16/0477

To the following model of personal protective equipment:

\* reference of the model:

16874

\* protective glove against

mechanical risks.

\* Manufacturer :

#### **ODIBI SRL**

Via Venezia, 35 - 33085 Maniago (PN), Italy

Italy

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on May 12th, 2016

Issued by Lionel GAUDILLERI

NB 0075

NOTA: Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.



# 1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index: 01

Reference: 16874

Basic Model

Dated: MAY, 2016

15 Gauge Nylon/Lycra Glove with Breathable Microfoam Nitrile Coating

#### Available sizes:

5 6 7 8 9 10 11

## Visual description:



#### Material:

	Color	Material	Gauges	Thickness
PALM	Black	Nitrile		0.1mm
FALIVI	Grey	nylon/lycra	15	
BACK	Grey	nylon/lycra	15	
LINING				
CUFF	Grey/ White	nylon/lycra/elastic	15	
BINDING	orange/ blue/ yellow/ red/ green/ white/ brown	polyester		



## 2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- \* EN 420:2003+A1:2009
- General requirements for gloves and test methods

\* EN 388:2003

- Protective glove against mechanical risks
- \* At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)
- \* This product is a category II.

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	СТС	Other
EN 420	S160402761_2 S151008522 S160403070	
Azo	S160402761_2 S151008522 S160403070	
EN 388	S160404090 S160402761_2	
OTHER	S160402761_2(PAHS, Tin, Cad) S160402760(DMFu)	

## Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
4	1	3	1

The levels of performance have been measured on the palm



# 3. MARKING

## Each glove is clearly marked with the following information:

- \* Logo of the authorized representative:
- \* ( € marking
- \* reference of the model:

16874

- \* size
- \* pictogram for mechanical risks followed by the performance levels
- \* information pictogram

## Marking example:





EN388:2003



## **ODIBI SRL**

# **MANUFACTURER'S TECHNICAL FILE**

Reference of the product : 16874

Technical file index : 01

Last update : MAY, 2016

# **IDENTIFICATION**

Reference of the product : 16874

Basic model

Technical file index:

Last update: MAY, 2016

### Manufacturer:

**ODIBI SRL** 

Via Venezia, 35 - 33085 Maniago (PN), Italy

Italy

tel: +39 0427 701211 - 71813

fax: +39 0427 700211

### Factory:

Fortes Industrial (Shanghai) Co., Ltd 913, Block A, No.58 East Xinjian Rd, Shanghai 201199 China PRC

tel: 0086 21 5783 2572 fax: 0086 21 5783 2892

# **GLOVE DESCRIPTION**

## Glove description:

15 Gauge Nylon/Lycra Glove with Breathable Microfoam Nitrile Coating

### Visual description:



## Available sizes :

Minimum length of glove (mm)	Sizes
210	5
220	6
230	7
240	8
250	9
260	10
270	11

## **Glove constitution:**

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
PALM		Black	Nitrile	230m2/g		0.1mm
		Grey	nylon/lycra	310m2/g	15	
BACK		Grey	nylon/lycra	310m2/g	15	
LINING						
CUFF		Grey/ White	nylon/lycra/elastic	410m2/g	15	
BINDING		orange/ blue/ yellow/ red/ green/ white/ brown	polyester			

# **PROTECTION SCOPE**

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

#### **GENERAL REQUIREMENTS**

#### Standard EN 420 : 2003 + A1 : 2009

Dexterity:

5

PH of glove and lining is greater than 3.5 and lower than 9.5:

yes

Chromium VI lower than the detection limit:

conform

Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

# SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

#### Mechanical hazard EN 388: 2003

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1

The levels of performance have been measured on the palm

## **TEST REPORTS**

Laboratory	СТС	Other
EN 420	S160402761_2 S151008522 S160403070	
Azo	S160402761_2 S151008522 S160403070	
EN 388	S160404090 S160402761_2	
OTHER	S160402761_2(PAHS, Tin, Cad) S160402760(DMFu)	

# **MARKING - PACKAGING**

#### Information printed on the glove:

Logo of the authorized representative :

Logo (€

Glove's reference: 16874

Size indicator

Pictograms related to risks against which protection is offered with performance levels Information pictogram

#### Marking example:









## Method of marking on the glove:

Heat Transfer Printing

#### Packaging:

1 pair per resealable polybag, 12 pairs per polybag, 144 pairs per carton

#### INSTRUCTION FOR USE

#### **ODIBI SRL**

Via Venezia, 35 - 33085 Maniago (PN), Italy

Italy

Glove reference: 16874

Available sizes: 5 6 7 8 9 10 11

#### Glove description:

15 Gauge Nylon/Lycra Glove with Breathable Microfoam Nitrile Coating

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

#### Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :



Application Mechanical hazard - EN 388





4131 Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)

#### Protection limit:

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entaglement by moving parts of machines.

#### Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.